

astron(elec·tron·ics)

verb: 1. representation defined

New Phone:

(714) 891-8971

sales@astron1.com

astron1.com

Lines Represented

Alpha & Omega
API Delevan
CSI Keyboard
E-Switch
EDI Diodes
Global Power
Globtek
L-Com
Methode
Micropac
SynQor
Tamura
Tocos
VCC
YS Tech

CELEBRATING
20
Years



TL3305 Series Ultraminiature Tact Switch

New SMT Tact is only 4.5 x 4.5mm

Switch Features

- 4.5mm x 4.5mm footprint
- Surface mount termination
- Two operating forces
- 500,000 life cycles
- Multiple actuator lengths



RoHS

SPECIFICATIONS

Electrical Rating: 50mA @ 12VDC
Electrical Life: 100 gf = 500,000 Cycles
200 gf = 200,000 Cycles
Contact Resistance: 100mΩ Max
Insulation Resistance: 100MΩ Min. at 100VDC
Dielectric Strength: 200VAC for 1 min.
Operating Temperature: -20°C to 70°C
Storage Temperature: -30°C to 90°C
Operating Force: 100 gf, 200 gf
Travel: 0.20mm
Contact Arrangement: SPST, normally open

FEATURES & BENEFITS

- Ultra-miniature 4.5 x 4.5mm
- Multiple actuator options
- Surface mount
- Multiple operating force options

TL3360 Series Right Angle Tact Switch

New Right Angle Tact is Surface Mount

Switch Features

- Multiple actuator lengths
- Surface mount termination
- Two operating forces
- 200,000 life cycles
- Right angle



RoHS

SPECIFICATIONS

Electrical Rating: 50mA @ 12VDC
Electrical Life: 100 gf = 100,000 Cycles
200 gf = 200,000 Cycles
Contact Resistance: 100mΩ Max
Insulation Resistance: 100MΩ Min. at 100VDC
Dielectric Strength: 200VAC for 1 min.
Operating Temperature: -20°C to 70°C
Storage Temperature: -30°C to 90°C
Operating Force: 100 gf, 200 gf
Travel: 0.20mm
Contact Arrangement: SPST, normally open

FEATURES & BENEFITS

- Ultra-miniature 4.5 x 4.5mm
- Multiple actuator options
- Surface mount
- Multiple operating force options

Note New Address:

5406 Bolsa Ave, Huntington Beach, CA 92649